# AV PRO CFexpress B XT MK2

CFexpress<sup>™</sup> 2.0 | Type B

660 GB 1320 GB





# CFexpress <sup>™</sup> 2.0 Type B

# Extended Card Endurance

for Demanding RAW Continuous Mode Photography and High-Bitrate Video

## Y2 Processor

Exceptional Processing Power for 12K+ RAW Video and Photo

# Stable Stream<sup>™</sup>

Uninterrupted Read/Write Performance throughout the Card's Capacity

# Advanced Thermal Management

Protects the Card against Overheating

## **Minimal Power Drain**

High Performance with Low Power Demand from Host Camera

## Host Power Loss Protection

# **Rock-Solid Build**

# Free Engraving Option

# In-House Data Recovery Service<sup>1</sup>

on Hard- and Software Level

0%

## GENERAL

Form Factor CFexpress<sup>™</sup> Type B

Capacities 660 GB | 1320 GB

 $\begin{array}{l} \textbf{Unit Dimensions} \\ 38.5\times3.8\times29.8 \text{ mm} \\ (1.52\times0.15\times1.17 \text{ in}) \end{array}$ 

**Unit Weight** ~ 7 g | 0.25 oz

## TECHNICAL

Interface CFexpress<sup>™</sup> 2.0 | Type B PCIe 3.0 ×2

**Features** Temperature Sensor, TRIM<sup>2</sup>, ECC, EMS Protection, SMART<sup>2</sup>, Power Management

## PERFORMANCE<sup>3</sup>

Maximum Speeds Read: 1785 MB/s Write: 1600 MB/s

Sustained Speeds Read: 1785 MB/s Write: 1480 MB/s

## RELIABILITY

Data Reliability Built-In EDC / ECC Function

**Certifications** CE, RoHS, FCC, UKCA, RCM, REACH, KC

## ELECTRICAL

DC Input Voltage 3.3 V ± 5 %

Power Usage (idle/max)Sleep< 50 mW</td>Idle0.45 WMax2.40 W

## ENVIRONMENTAL

Shock Resistance Operating: 50 G

**Vibration Resistance** Operating: 15 G

**Temperature Resistance** Operating: -10 °C | 70 °C 14 °F | 158 °F

Storage: -20°C|85°C -4°F|185°F

**Operating Humidity** 5 % to 95 % Non-Condensing

## WARRANTY

3-Year Limited Warranty

## PACKAGE CONTENT

AV PRO CFexpress B XT MK2

RETAIL PACKAGING DETAILS

**Box Dimensions** 113 × 23 × 132 mm (4.45 × 0.91 × 5.2 in)

**Box Weight** ~ 60 g | 2.12 oz

#### ORDERING INFORMATION

#### 660 GB

SKU AVP660CFXBMK2XT EAN 9120056585939 UPC 812937024758

## 1320 GB

SKU AVP1T3CFXBMK2XT EAN 9120056585946 UPC 812937024765

- Data recovery service exclusively provided by Angelbird in Austria.
- <sup>2</sup> TRIM and SMART support depending on the OS used.
- <sup>3</sup> Speeds based on internal testing. Actual transfer rates and capacity may vary depending on system hardware and other factors. 4K, 6K, 8K, 12K+, and Full HD support may vary depending on host device, file attributes, and other factors.
- <sup>4</sup> Visit angelbird.com/warranty and activate your 3-year limited warranty within 30 days of purchase.

© 2023 Angelbird Technologies GmbH Angelbird is a registered trademark of Angelbird Technologies. All rights reserved.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

Specifications are subject to change without notice. Specifications are provided "as is" without warranty of any kind.

202307071050

1800 MB/s 14400 Mbit/s AV PRO CFexpress B XT MK2 Stable Stream<sup>™</sup> Sustained Write Performance 1480 MB/s 11840 Mbit/s Actual Write Requirements Nikon Z 9 45.7MP 20p RAW Burst Lossless 1200 MB/s 9600 Mbit/s 1000 MB/s Actual Write Requirements 8000 Mbit/s RED V-RAPTOR 8K RAW 120p 850 MB/s 6800 Mbit/s 500 MB/s 4000 Mbit/s 300 MB/s 2400 Mbit/s ANGELBIRD BRAND X BRAND Y 100 MB/s \_ 800 Mbit/s

50%



MADE IN AUSTRIA



