

ATOMX SSDmini KIT  
BY ANGELBIRD



C R E

A T E

ANGELBIRD.COM



DEVELOPED FOR  
ATOMOS 4K WORKFLOWS

## PUSHING THE BOUNDARIES OF TECHNOLOGIES AND INNOVATION

AtomX SSDmini DELIVERS PROFESSIONAL GRADE RECORDING MEDIA IN A REDUCED SSD FORM FACTOR. GET THE SAME ROBUST, RELIABLE, HIGH PERFORMANCE OF OUR TRADITIONAL SATA SSD MEDIA - BUT SMALLER. AtomX SSDmini GIVES YOU THE CONFIDENCE TO PUSH YOUR CREATIVE POTENTIAL.

### SPECIFICATIONS AND FEATURES



#### Developed for ATOMOS

NINJA V | NINJA FLAME | NINJA INFERNO |  
SUMO 19\* | SUMO 19M\* | SHOGUN FLAME |  
SHOGUN INFERNO | SHOGUN STUDIO\*



ESD & overload protection



4k60p 2k240p Apple ProRes / Avid DNx  
5.7k30p 4k60p 2k240p Apple ProRes RAW  
4k30p CDNG



Solid Grip™, Shock & temperature proof



500 GB | 1 TB | 2 TB



Power smoothing



Stable Stream™



CNC-worked aluminium casing



Speed	Read	Write
Sustained	540 MB/s	500 MB/s
Sequential	560 MB/s	520 MB/s



Rock-solid build



X-ray & magnetic proof

## SPECIFICATIONS / ORDERING

### GENERAL SPECIFICATIONS

**Capacity**  
500 GB | 1 TB | 2 TB

**Dimensions**  
80 × 75.5 × 9.3 mm  
(3.15 × 2.97 × 0.37 in)

**Form Factor**  
SSDmini

**Weight**  
~ 90.0 g | ~3.17 oz

### TECHNICAL SPECIFICATIONS

**Interface**  
SATA 6 Gb/s, 3 Gb/s and 1.5 Gb/s  
supported  
SATA 3.0 compliant

**Over provisioning**  
~ 9 %

**Features**  
Temperature sensor, overload protection, TRIM, ECC, EMS protection, built-in cache, SMART, NCQ

### PERFORMANCE SPECIFICATIONS

**Sustained Read Speed<sup>1</sup>**  
up to 540 MB/s  
**Sustained Write Speed<sup>1</sup>**  
up to 480 MB/s

**Sequential Read Speed<sup>1</sup>**  
up to 560 MB/s  
**Sequential Write Speed<sup>1</sup>**  
up to 500 MB/s

**Access Time (R/W)**  
~ 65 µs / 40 µs

### RELIABILITY SPECIFICATIONS

**MTBF**  
> 2,400,000 hours

**Data Reliability**  
Built-in EDC | ECC function

**Data Retention**  
10 years at 25°C

**Endurance**  
500 GB: 1,500 TBW  
1 TB: 3,000 TBW  
2 TB: 6,000 TBW

**Certifications**  
RoHS, FCC and CE compliant,  
REACH

### ELECTRICAL SPECIFICATIONS

**DC input voltage**  
5V ± 10%

**Power usage (idle | max)**  
500 GB: 0.35 W | 3.0 W  
1 TB: 0.35 W | 3.5 W  
2 TB: 0.35 W | 3.5 W

### ENVIRONMENTAL SPECIFICATIONS

**Shock resistance (operating)**  
1000 G/0.5ms

**Vibration resistance (operating)**  
2.17 GRMS

**Operating Temperature**  
-20 °C ~ +70 °C

**Storage Temperature**  
-40 °C ~ +85 °C

**Operating Humidity**  
5 % to 95 % non-condensing


### COMPATIBLE WITH<sup>3</sup>

NINJA V  
NINJA FLAME  
NINJA INFERNO  
SUMO 19\*  
SUMO 19M\*  
SHOGUN FLAME  
SHOGUN INFERNO  
SHOGUN STUDIO\*  
\*only with Atomos SSDmini Adaptor

A  
t  
o  
m  
X  
S  
S  
D  
m  
i  
n  
i  
K  
I  
T

# C-SATA TYPE-C TO SATA ADAPTER

A  
t  
o  
m  
X  
S  
S  
D  
m  
i  
n  
i  
K  
I  
T



EASY TO HANDLE, LIGHTWEIGHT AND DURABLE 2.5" AND 3.5" SATA STORAGE ACCESS WITH LATEST USB 3.1 GEN 2 10GB/S CONNECTIVITY. THANKS TO THE ADAPTER'S HOT PLUG FUNCTIONALITY, YOU CAN EASILY SWAP YOUR SSD/HDD WITHOUT THE NEED OF BUILDING THE DRIVE INTO YOUR DESKTOP OR LAPTOP COMPUTER. BACKING UP, CLONING, OR EVEN EDITING ON THE GO IS HASSLE FREE AND EFFICIENT. WITH NATIVE SATA 3 SPEED SUPPORT OF UP TO 6GB/S AND ITS LOW LATENCY, FILE TRANSFERS ARE RELIABLE AND LIGHTNING FAST.



USB-C to SATA 3, 6Gb/s  
USB-C 3.1 Gen 2, 10Gb/s



TRIM support<sup>2</sup>



Additional 12V power  
for 3,5 HDD powering<sup>1</sup>



Mac | Windows | Linux | Android




UASP support



USB-C



SATA

<sup>1</sup> 12V Power supply not included  
Power input 12V | 3.5 x 1.1mm 

<sup>2</sup> For detailed information about TRIM support, please visit  
[www.angelbird.com/support](http://www.angelbird.com/support)

ATOM X SSDmini

# USB TYPE A TO TYPE C ACTIVE ADAPTER



A  
t  
o  
m  
X  
  
S  
S  
D  
m  
i  
n  
i  
  
K  
I  
T

UP OR DOWN? IT DOESN'T MATTER. THE ADAPTER'S IMPLEMENTED ACTIVE SWITCHING LOGIC PROVIDES YOU WITH THE MOST OBVIOUS AND PRACTICAL ADVANTAGE OF ANY USB-C PLUG. IT CAN BE PLUGGED IN WHICHEVER WAY YOU WANT, UP OR DOWN. THUS, ALL OF THE ANNOYING FUMBLING, AS WITH CONVENTIONAL USB PLUGS, HAS BEEN ELIMINATED!



USB 3.1, Gen 2 10Gb/s  
Type-A to Type-C



42 × 15 × 7.5 mm  
(1.65 × 0.59 × 0.29 in)



Active switching logic



3-year limited warranty<sup>3</sup>



UASP support



Mac | Windows | Linux | Android



TRIM support

ATOMX SSDmini

Specifications are subject to change without notice.  
Specifications are provided "as is" without warranty of any kind.  
201903051033

SPECIFICATIONS / ORDERING

A  
t  
o  
m  
X  
  
S  
S  
D  
m  
i  
n  
i  
  
K  
I  
T

WARRANTY<sup>2</sup>

3-year limited warranty  
or TBW threshold exceeded

PACKAGE CONTENT

- AtomX SSDmini
- USB-A-C Adapter
- C-SATA Adapter
- Activation code for the full limited warranty and additional free software licenses and content

RETAIL PACKAGING DETAILS

Box dimension  
113.0 × 105.0 × 20.0 mm  
(4.45 × 4.13 × 0.79 in)

Weight  
~ 170.0g | ~5.98 oz

<sup>1</sup> Speed based on internal testing.  
Actual transfer rates and capacity may vary depending on the product model, system hardware and other factors.


<sup>2</sup> To receive the full limited warranty, the product needs to be registered on the Angelbird Personal Service Portal within 30 days after purchase. If not registered within this period, the market-specific legal guarantee period comes into force.

<sup>3</sup> For an up-to-date compatibility list, please visit the product site at [www.angelbird.com](http://www.angelbird.com)

Mac® is a registered trademark of Apple Inc.  
Windows® is a registered trademark of Microsoft Corp.  
Linux® is a registered trademark of Linus Torvalds.  
Android™ is a registered trademark of Google Inc.  
Atomos® is a registered trademark of Atomos Global Pty. Ltd.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

ORDERING INFORMATION

	Capacity	SKU	EAN	UPC
●	500 GB	ATOMXMINI500PK-KIT	9120056584406	812937023225
●	1 TB	ATOMXMINI1000PK-KIT	9120056584413	812937023232
●	2 TB	ATOMXMINI2000PK-KIT	9120056584420	812937023249